



The Difference Is Performance!

DRILL POINT QUATTRO NOZZLE

Penetrating ability and traction characteristics for tough clogs

The Drill Point Quattro Nozzle is a terrific tool for removing total line blockages. The stainless steel drill tip penetrates the toughest clogs, particularly grease blockages. The three jets pre-drilled in the changeable tip then enlarge the opening in the clog, working with the sharp, tapered edges of the Drill Point Quattro.

The loosened debris is then washed down the line by the propulsion jets at the back of the Drill Point Quattro that provide excellent thrust. For low maintenance, high performance penetrating nozzle, the Drill Point Quattro is hard to beat. The Drill Point Quattro is classified as a Tier One or Tier Two Nozzle depending on the size and the availability of replaceable inserts. Inserts are available in steel or titanium ceramic.



ADVANTAGES

- Replaceable Drill Point
- Excellent Thrust & Traction
- Cost Competitive; Tier One & Tier Two Nozzle
- Replaceable Inserts Available

APPLICATIONS

- **SANITARY**
- Total Blockages
- Grease Penetration
- Pipes from 2"+

KEG DRILL POINT QUATTRO NOZZLE

Product Shown Above	Part Number	Hose Size	Number of Inserts	Insert Size	Weight (pounds)	Dimensions	Pipe Size
A	100051-S	1/4"	Factory	Drill	.2	1 7/8" x 7/8"	From 2"
A	100053-S	3/8"	Factory	Drill	.3	1 7/8" x 7/8"	From 2"
B	100055-S	1/2"	Factory	Drill	.4	2 1/4" x 1 1/4"	From 3"
C	100057	3/4"	6	M6	.8	3 7/8" x 1 7/8"	From 3"
D	100059	1"	6	M6	1.9	4 7/8" x 2 3/8"	From 4"

Please indicate "-C" for titanium ceramic inserts or "-S" for steel inserts after each part number for 3/4" and 1". The 1/2", 3/8", and 1/4" are only offered with factory steel inserts.