

TOLIET TAMER NOZZLE

Available in Aluminum
or Stainless Steel

ADVANTAGES

- Residential Friendly
- Virtually Eliminates Blowing Toilets
- Use with as Low as 50 GPM
- Custom Tuned to Your Jetting Specifications
- Replaceable Titanium Ceramic Inserts Available

APPLICATIONS

- **SANITARY, SEWER**
- Effectively Clean Problem Lines
- Save Time & Money by Reducing Residential Clean up
- Shallow Pipe Lines with Blowing/Sucking Events
- Excellent General Cleaning Nozzle



Aluminum Toliet Tamer
Nozzle requires skid.

TECHNICAL SPECIFICATIONS

- 6 Propulsion Jets 1 Forward Jet
- Replaceable Titanium Ceramic Inserts
- 30° and 40° Jet Angles
- Available in Stainless Steel or Aluminum

QUICK FACTS:

- Flow Range: 50 GPM - 130 GPM
- Pressure Range: 1000 PSI - 3000 PSI

Product Shown Above	Part Number	Hose Size	Number of Inserts	Insert Size	Dimensions	Weight (pounds)	Pipe Size
A	100115WA	1"	6 Rear 1 Front	M8	4 1/4" X 2 3/4"	3.5	4" to 12"
B	100115WAA	1"	6 Rear 1 Front	M8	4 1/4" X 2 3/4"	1.5	4" to 12"