

TURBO & MICRO CHAIN CUTTERS

ADVANTAGES

- Easily Configured for Multiple Jobs
- Use in Sweeping 90 Degree or 45 Degree Elbows
- Product Includes: Carrying Case, Tools and Owner's Manual
- Clean with Soap and Water

APPLICATIONS

- **SANITARY**
- 2", 3", 4" Pipes (6" w/Optional Skid)*
- Plumbing Applications
- Offsets, Pipe Rips, Services, Laterals, Small Pipes
- Root Removal in Laterals & Sanitary Service Lines
- Scale and Rust Removal
- Use with 1/2" hose*
- 5" Swivel Included

TECHNICAL SPECIFICATIONS

- No Skid Required for 2" & 3" Applications
- Individual Skid for 4" Micro Applications Included
- Individual skid for 6" Applications*
- Pump minimum of 8 GPM & 1700 PSI Required
- Tier Two Nozzle
- Titanium Ceramic Inserts Included
- Additional 5" of Chain Included
- Pulling Device Available*
- 90 Degree Lateral Applications Should Not Utilize the Guide Carriage Skids
- Reducer and Leader Hose Sold Separately



B

** See accessories section for available products sold separately.*

QUICK FACTS:

- Pipe Range: 2" up to 6"
- Flow Range: 8 GPM+
- Pressure Range: 1700 PSI - 4000 PSI
- Hose Sizes: 3/8"-1/2"

Product Shown Above	Part Number	Hose Size	Number of Inserts	Insert Size	Weight (pounds)	Dimensions	Pipe Size
A	200110	1/2"	3 Rear/ 3 Rotating	M6	1.2	3 7/8" x 1 1/2"	2" to 6"
B	200110-T	1/2"	3 Rear/ 2 Rotating	M6	1.2	3 7/8" x 1 1/2"	2" to 6"

Titanium ceramic inserts are recommended for use with Chain Cutters